

DAHİLİ TESİSAT TELEFON KABLOLARI
INTERNAL TELEPHONE CABLES

EMEK KABLO HBH/HBH-K

HBH / HBH-K



1 - 200 çiftli kablolar / 1 - 200 pair cables

KULLANIM ALANLARI

Bina içi tesisatlarda sinyal iletişiminde kullanılır.

KABLO YAPISI

İletken Çapı	0,50mm mono çıplak ve ya kalaylı elektrolitik bakır tel
İzoleli Çap	0.95mm LSOH
Dış Kılıf	Gri veya krem LSOH. (BS 6746 Type-3)

ELEKTİRİKSEL ÖZELLİKLER

İletken Direnci (1 km)	max. 97.8 ohm
Etkin Kapasite (1 km)	max 120 nF

APPLICATION

These cables used inside buildings for signal transmission purposes.

CONSTRUCTION

Conductor Diameter	0.50mm solid bare or tinned solid copper wire.
Insulated Diameter	0.95mm LSOH
Outer sheath	Grey or cream LSOH. (BS 6746 Type-3)

ELECTRICAL CHARACTERISTICS

Conductor resistance (1 km)	max. 97.8 ohm
Effective capacity (1 km)	max 120 nF

0.50mm.

KOD NO. CODE NO.	İLETKEN ADEDİ VE ÇAPI INSULATED NR OF CONDUCTOR AND DIAMETER mm.	KABLO ÇAPI OVERALL DIAMETER mm.	YAKLAŞIK AĞIRLIK APPROX. WEIGHT kg/km	STANDART UZUNLUK STANDARD LENGTH mt
42405001/42505001	1x2x0,50	3,5	16	100/3000
42405002/42505002	2x2x0,50	4,3	25	100/3000
42405004/42505004	4x2x0,50	5,4	40	100/2000
42405006/42505006	6x2x0,50	6,5	56	100/1000
42405010/42505010	10x2x0,50	7,25	84	100/1000
42405015/42505015	15x2x0,50	8,6	111	100/500
42405020/42505020	20x2x0,50	10	146	100/500
42405030/42505030	30x2x0,50	12	218	100/250
42405050/42505050	50x2x0,50	14,5	324	100/250
42405100/42505100	100x2x0,50	20	613	100/250
42405150/42505150	150x2x0,50	24	910	100/250
42405200/42505200	200x2x0,50	28	1290	100/250