

CAT.6A U/UTP 500 MHZ



KULLANIM ALANLARI

ISDN - VoIP
 TOKEN RING 4/16 Mbit - 100 VG-AnyLAN
 TP-PMD / TP-DDI - ATM 155, 622, 1200 Mbit
 ETHERNET: 10 Base T, 100 Base Tx, 100 Base T4, 1000 Base T, 10 G Base T
 IEEE 802.3af - PoE (Power Over Ethernet)

KABLO YAPISI

İletken	Mono tavlı bakır AWG23
İzolasyon	PO - Poliolefin
Separatör	PO - Poliolefin
Kılıf	PVC veya LSZH - 5024 Mavi RAL
Standartlar	IEC 61156-5 / EN 50288-11-1

TEKNİK ÖZELLİKLER

Direnç (max)	75 Ω / km
Empedans	1-100 MHz 100 \pm 15 Ω / 100-250 MHz 100 \pm 20 Ω 250-500 MHz 100 \pm 25 Ω
Kapasite	Nominal 48 pF/m
Yayıma Hızı	69% c

APLICATION

ISDN - VoIP
 TOKEN RING 4/16 Mbits - 100 VG-AnyLAN
 TP-PMD/TP-DDI - ATM 155, 622, 1200 Mbits
 ETHERNET: 10 Base T, 100 Base Tx, 100 Base T4, 1000 Base T, 10 G Base T
 IEEE 802.3af - PoE (Power Over Ethernet)

CONSTRUCTION

Conductor	Solid annealed copper AWG23
Insulation	PO - Polyolefin
Separator	PO - Polyolefin
Jacket	PVC or LSZH - Blue RAL 5024
Standarts	IEC 61156-5 / EN 50288-11-1

TECHNICAL SPECIFICATIONS

Resistance (max)	75 Ω / km
Impedance	1-100 MHz 100 \pm 15 Ω / 100-250 MHz 100 \pm 20 Ω 250-500 MHz 100 \pm 25 Ω
Capacitance	Nominal at 48 pF/m
Velocity Of Propagation	69% c

MHz	INSERTION LOSS (dB/100 m)	NEXT (dB/100 m)	ACR-N (dB/100 m)	PSNEXT (dB/100 m)	ACR-F (dB/100 m)	PSACR-F (dB/100 m)	RETURN LOSS (dB/100 m)
1	2.1	74.3	72.3	72.3	67.8	64.8	20.0
4	3.8	65.3	61.5	63.3	55.8	52.8	23.0
10	5.9	59.3	53.3	57.3	47.8	44.8	25.0
16	7.5	56.2	48.6	54.2	43.7	40.7	25.0
25	9.4	53.3	43.8	51.3	39.8	36.8	24.3
31.25	10.5	51.9	41.2	49.9	37.9	34.9	23.6
100	19.1	44.3	24.5	42.3	27.8	24.8	20.1
200	27.6	39.8	10.8	37.8	21.8	18.8	18.0
250	31.1	38.3	5.5	36.3	19.8	16.8	17.3
300	34.3	37.1	-	35.1	18.3	15.3	16.8
500	45.3	33.8	-	31.8	13.8	10.8	15.2