

DAHİLİ TESİSAT TELEFON KABLolari
INTERNAL TELEPHONE CABLESVBV / VBV-K
(TS IEC 60189-2)

1 - 200 çiftli kablolar / 1 - 200 pair cables

KULLANIM ALANLARI

Bina içi tesisatlarda sinyal iletişimde kullanılır.

KABLO YAPISI

İletken çapı | 0,50mm mono çıplak ve ya kalaylı elektrolitik bakır tel
İzoleli çap | 0.95mm Yarı-sert PVC, (BS 6746 Type-1)
Dış kılıf | Gri veya krem PVC. (BS 6746 Type-3)

ELEKTİRİKSEL ÖZELLİKLER

İletken Direnci (1 km) | max. 97.8 ohm
Etkin Kapasite (1 km) | max 120 nF

APLICATION

These cables used inside buildings for signal transmission purposes.

CONSTRUCTION

Conductor Diameter | 0.50mm solid bare or tinned solid copper wire.
Insulated Diameter | 0.95mm Semi-rigid PVC. (BS 6746 Type-1)
Outer sheath | Grey or cream PVC. (BS 6746 Type-3)

ELECTRICAL CHARACTERISTICS

Conductor resistance (1 km) | max. 97.8 ohm
Effective capacity (1 km) | max 120 nF

0.50mm.

| KOD NO. CODE NO. | İLETKEN ADEDİ VE ÇAPI INSULATED NR OF CONDUCTOR AND DIAMETER mm. | KABLO ÇAPI OVERALL DIAMETER mm. | YAKLAŐIK AĐIRLIK APPROX. WEIGHT kg/km | STANDART UZUNLUK STANDARD LENGTH mt |
|---------------------|--|---------------------------------------|---|---|
| 40905001/41005001 | 1x2x0,50 | 3,5 | 16 | 100/3000 |
| 40905002/41005002 | 2x2x0,50 | 4,3 | 25 | 100/3000 |
| 40905004/41005004 | 4x2x0,50 | 5,4 | 40 | 100/2000 |
| 40905006/41005006 | 6x2x0,50 | 6,5 | 56 | 100/1000 |
| 40905010/41005010 | 10x2x0,50 | 7,25 | 84 | 100/1000 |
| 40905015/41005015 | 15x2x0,50 | 8,6 | 111 | 100/500 |
| 40905020/41005020 | 20x2x0,50 | 10 | 146 | 100/500 |
| 40905030/41005030 | 30x2x0,50 | 12 | 218 | 100/250 |
| 40905050/41005050 | 50x2x0,50 | 14,5 | 324 | 100/250 |
| 40905100/41005100 | 100x2x0,50 | 20 | 613 | 100/250 |
| 40905150/41005150 | 150x2x0,50 | 24 | 910 | 100/250 |
| 40905200/41005200 | 200x2x0,50 | 28 | 1290 | 100/250 |