

110Ω DIJITAL AUDIO&IŞIKLANDIRMA KABLolari 110Ω DIGITAL AUDIO&LIGHTING CABLES



KULLANIM ALANLARI

Ekranlama Özellikleri ve kesit seçenekleriyle 110Ω Dijital AES/EBU ve DMX kablolarla ilgili size çok geniş bir ürün yelpazesi sunuyoruz.

MEKANİK ÖZELLİKLER

Min. Bükme Yarıçapı	Sabit Tesis	10 x Dış Çap
	Hareketli Tesis	15 x Dış Çap
Çalışma Sıcaklığı	Sabit	-25°C +70°C
	Hareketli	-5°C..... 70°C

ELEKTİRİKSEL ÖZELLİKLER/ELECTRICAL CHARACTERISTICS

	İLETKEN DİRENCİ CONDUCTOR RESISTANCE	EKRAN DİRENCİ SHIELD RESISTANCE	KAPASİTE (İLETKEN/İLETKEN) CAPACITANCE (COND/COND)	KAPASİTE (İLETKEN/EKRAN) CAPACITANCE (COND/SCREEN)
EK.203DAI	< 152 Ohm / km	< 65 Ohm / km	45 pF / mt.	84 pF / mt.
EK.204DAS	< 87 Ohm / km	< 24 Ohm / km	46 pF / mt.	86 pF / mt.
EK.204DHAS	< 87 Ohm / km	< 24 Ohm / km	46 pF / mt.	86 pF / mt.
EK.206AES	< 85 Ohm / km	< 24 Ohm / km	46 pF / mt.	86 pF / mt.
EK.205DMX	< 85 Ohm / km	< 35 Ohm / km	46 pF / mt.	86 pF / mt.
EK.305DMX	< 53 Ohm / km	< 24 Ohm / km	85 pF / mt.	150 pF / mt.
EK.407DMX	< 56 Ohm / km	< 12 Ohm / km	65 pF / mt.	120 pF / mt.
EK.407HDMX	< 56 Ohm / km	< 12 Ohm / km	65 pF / mt.	120 pF / mt.
EK.A1P3	< 85 Ohm / km	< 22 Ohm / km	47 pF / mt.	86 pF / mt.
EK.DMXPOWER	< 87 Ohm / km	< 24 Ohm / km	46 pF / mt.	86 pF / mt.

AES/EBU KABLolari/AES/EBU CABLES

SEMBOL SYMBOL	ÜRÜN KODU CODE NO.	KESİT CROSS SECTION	KILIF MALZEMESİ JACKET MATERIAL	DIŞ ÇAP OVERALL DIAMETER	STANDART AMBALAJ STANDARD LENGTH
EK.203DAI	21134203	1x2x0,12mm ²	PVC	3,00	1000m
EK.204DAS	21752204	1x2x0,22mm ²	PVC	4,80	100/1000m
EK.204DHAS	21752204.H	1x2x0,22mm ²	LSZH	4,20	100/1000m
EK.206AES	21652206	1x2x0,22mm ²	PVC	6,35	100/1000m

AES/EBU DMX KABLolari/AES/EBU DMX CABLES

SEMBOL SYMBOL	ÜRÜN KODU CODE NO.	KESİT CROSS SECTION	KILIF MALZEMESİ JACKET MATERIAL	DIŞ ÇAP OVERALL DIAMETER	STANDART AMBALAJ STANDARD LENGTH
EK.205DMX	21623206	1x2x0,22mm ²	PVC	5,80	1000m
EK.305DMX	21623207	1x2x0,34mm ²	PVC	5,80	1000m
EK.407DMX	21623407	2x2x0,34mm ²	PVC	7,00	1000m
EK.407HDMX	21623407.H	2x2x0,34mm ²	LSZH	7,00	1000m
EK.A1P3	22631205	1x2x0,22mm ² +3G1,50mm ²	PVC	9,80	Özel uzunluk/Custom length
EK.DMXPOWER	22631206	1x2x0,22mm ² +3G1,50mm ²	PVC	15,50	Özel uzunluk/Custom length

APPLICATION

Emek Kablo presents a large product range of 110Ω digital AES/EBU and DMX cables.

MECHANICAL CHARACTERISTICS

Min. Bending Radius	Fixed Installation	10 x Overall Diameter
	Mobile Use	15 x Overall Diameter
Temperature Range	Static	-25°C +70°C
	Flexing	-5°C..... 70°C